

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2020/878

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture
Substance/Mixture: Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified use: Refrigerant gas.

1.3. Details of the supplier of the safety data sheet

Producer/Supplier: Frigostar Refrigerants Kft.
Address: H-6763 Szatymaz Kossuth u. 12.
Phone: +36-62-283-481
Fax: +36-62-583-550
E-mail: info@vrec-co.hu

1.4. Emergency telephone number:

Austria tel.: +431 406 43 43, Belgium tel.: 070/245.245, Bulgaria tel.: +359 2 9154 409, Czech Republic tel.: +420 224 919 293, +420 224 915 402, Denmark tel.: 82 12 12 12, Estonia tel.: 112, Finland tel.: (09) 471 977 (direct) or (09) 4711 (exchange), France tel.: ORFILA (INRS) : + 33 (0)1 45 42 59 59, Ireland tel.: 01 809 2166, Lithuania tel.: +370 5 236 20 52, +370 687 53378, Malta tel.: 2545 0000, Medicines & Poisons Info Office tel.: 2545 6504, Norway tel.: 22 59 13 00, Portugal tel.: 808 250 143, Romania tel.: 021.318.36.06 (8:00 - 15:00), Slovakia tel.: +421 2 5477 4166, Spain tel.: + 34 91 562 04 20, Sweden tel.: 112; 08-331231 (9:00-17:00).

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture:

Regulation (EC) No 1272/2008 (CLP):

Physical hazards: Flammable gases – Category 1 (Flam. Gas. 1, H220)
Gases under pressure – Liquefied gas (Press. Gas, H280)

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



2.2 Label elements:

Regulation (EC) No 1272/2008:

Pictograms:



Signal word:

Danger

Hazard statements:

- H220 Extremely flammable gas.
H280 Contains gas under pressure; may explode if heated.

Precautionary statements, storage:

- P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 Eliminate all ignition sources if safe to do so.
P403 Store in a well-ventilated place.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

- Physical hazards: Liquefied gas. Being heavier than air, gases may accumulate in lower and/or confined spaces when released.
The PBT-, and vPvB-assessment see in section 12.
- Endocrine effects: The mixture does not contain any endocrine disrupting substances included in the list established per Article 59 (1).

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



SECTION 3: Composition/information on ingredients

3.2. Mixtures

Components	EC number	REACH number	CAS number	Index number	Weight %	Classification (Regulation (EC) No 1272/2008)	SCL, ATE, M-factor
Isobutane	200-857-2	01-2119474691-32	75-28-5	601-004-00-0	≤ 50	Flam. Gas 1, H220 Press. Gas (Liq) H280	-
Propane	200-827-9	01-2119486944-21	74-98-6	601-003-00-5	≤ 50	Flam. Gas 1, H220 Press. Gas (Liq) H280	

H-statements see 16 section below.

SECTION 4: First aid measures

4.1. Description of first aid measures

Medical intervention: Call physician in case of asphyxiation, frostbite or burn.

Inhalation: Move victim to fresh air and to a safe place and take measures to prevent fire and explosion. Rescue personnel may need breathing apparatus. Let victim lay in rest and muffled. If breathing has stopped, apply artificial breathing or breathing apparatus. If victim is unconscious, lay him on his side in a stable position. Get medical help on site.

Ingestion: Ingestion is not considered a potential route of exposure.

Skin contact: Wash affected area with water. Contaminated clothes, rings, watch should be removed only if they are not adhered to the skin. Warm affected area slowly.

– frostbite

Eye contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Obtain medical assistance.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation: The substance has anesthetic effect, 1% (1000 ppm) causes sleepiness within a few minutes.
In concentrations higher than 10%: narcotic effect: weakness, headache, nausea, dizziness, confusion, blurred sight, increasing sleepiness.
Very high concentrations may cause unconsciousness, spasms and finally asphyxia caused by the absence of oxygen.

Ingestion: Ingestion is not considered a potential route of exposure.

Skin contact: Frostbite causes by the liquid state.

Eye contact: Frostbite causes by the liquid state.

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



Delayed effects: Not expected.
General: No information.

4.3. Indication of any immediate medical attention and special treatment needed

Advice for physician: Symptomatic treatment is recommended .
Special equipment at the workplace: Not necessary.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Applicable extinguishing media Dry chemical powder, foam, carbon dioxide, sand.

Not applicable extinguishing media High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Specific risk: Exposure to fire may cause containers to rupture/explode.
Special exposure hazards, combustion product, gases formed at combustion: carbon dioxide, carbon monoxide, hydrocarbons.

5.3. Advice for firefighters

Special protective equipment: Respiratory protective devices. (EN 14593-1), protective clothing against liquid chemicals. (EN 14605).

Advice: If possible, stop flow of product.
Move away from the container and cool with water from a protected position.
Use self-contained breathing apparatus and chemically protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal emergency procedures: Evacuate the area.
Extinguish all ignition sources! Try to stop the release!
Wear a self-contained breathing apparatus when entering the area unless atmosphere is proved to be safe. The affected area in the direction of the wind and other personnel carrying out damage control does not stay! The evacuation of persons facing the wind to be performed, have to wear respiratory protective device (EN 14593).
Ensure adequate air ventilation.

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



6.2. Environmental precautions

Environmental precautions: Try to stop release. Land of the danger area should be closed. High safety zone must be established. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify the authorities.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up: Ventilate area.

6.4. Reference to other sections

Personal protective equipment: See the Section 8.

Waste management: See the Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Recommendations for safe handling: This product should be used by properly trained person! Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. See more in Section 8.

Fire and explosion protection: Keep in a well-ventilated place, away from heat and ignition sources, electrostatic sources, strong oxidizers and high pressure oxygen. Prevent electrostatic discharges. Smoking is not allowed!

Hygiene standards: The people in contact with product should be maintained the workplace hygiene standards. After the treatment of the product at breaks, before eating, after work the hot hand and face washing is necessary.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures / Storage conditions: Can only be stored in a closed system, should be checked regularly for tightness. Store only in the original packaging. Tightly closed. Protect from sunlight and sources of heat. The bottles, containers are stored in an upright position, so as to prevent any contact with the liquid phase from the gas phase designed parts. Do not allow the temperature to rise above 50 ° C. After use, close the air outlet of the valve.

Incompatible materials: Strong oxidizing agents, high-oxygen-containing materials.

7.3. Specific end use(s)

Special uses: None.

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Component	CAS-NUMBER	Limit value, Eight hours (mg/m ³)	Limit value, Short term (mg/m ³)	Country
Propane	74-98-6	1800	3600	Austria
		1000	-	Belgium
		1800	3600	Denmark
		1800	7200	Germany (AGS)
		1800	7200	Germany (DFG)
		1800	-	Poland
		1000 (ppm)		Spain
		1800	7200	Switzerland
Isobutane	75-28-5	2400	9600	Germany (AGS)
		2400	9600	Germany (DFG)
		1900	-	Switzerland

8.2. Exposure controls

Engineering measures:

Do not inhale the gas! Avoid contact with liquefied gas with eyes or skin! Provide adequate ventilation! Only in closed, leak-proof network. No smoking, open flames and ignition sources related activities are prohibited!

Hygiene standards:

The people in contact with product should be maintained the workplace hygiene standards. After the treatment of the product at breaks, before eating, after work the hot hand and face washing is necessary.

Personal protective equipment

Eye and face protection:

Safety glasses with side-shields (EN 166) or face shield recommended to wear.

Skin protection

Hand protection:

Avoid hand contact. Proper contact is recommended to wear gloves to protect against cold (EN 511).

Other:

Long-sleeved clothing and anti-static anti-static footwear (EN ISO 2345) must be wear.

Inhalation protection:

In gas leak case, compressed air breathing apparatus (EN 14593) is recommended.

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



Environmental exposure controls

Environmental exposure control : Prevent from entering sewers, surface waters or soil.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical condition (20°C): Gas
 Colour: Colourless gas
 Odour: Characteristic odor.

Properties

Value

pH (20°C):	Not applicable.
Melting point / Freezing point:	No information.
Initial boiling point and boiling range:	No information.
Fire point:	No information.
Evaporating rate:	No information.
Flammability:	Extremely flammable.
Upper / lower flammability or explosive limits	
– lower explosive limit:	No information.
– upper explosive limit:	No information.
Vapor Pressure (40°C):	No information.
Vapor density:	
Relative density, gas:	2.05 (air=1) (Isobutane)
Relative density, liquified gas:	No information.
Solubility	
– In water:	No information.
– Organic solvents:	No information.
Partition coefficient: n-octanol/water:	No information.
Auto-ignition temperature:	No information.
Decomposition temperature:	No information.
Kinematic viscosity:	No information.
Explosive properties:	No information.
Oxidizing properties:	Not oxidising.

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



9.2. Other information

No information.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity: No specific reactivity other than those specified under section 10.5.

10.2. Chemical stability

Stability: Stable in the recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: There are no under normal conditions of use.

10.4. Conditions to avoid

Situations to avoid: Radiating heat, open flame, all ignition sources, sparks.

10.5. Incompatible materials

Materials to avoid: Strong oxidizers.

10.6. Hazardous decomposition products

Hazardous decomposition products: By thermal decomposition: Carbon dioxide, carbon monoxide, hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity:

- Skin: Not classified as hazardous.
- Inhalation: Not classified as hazardous.
- Ingestion: Not classified as hazardous.

Skin corrosion/irritation: Not classified as hazardous.

Serious eye damage/irritation: Not classified as hazardous.

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



Respiratory or skin sensitisation: Not sensitising.

Germ cell mutagenicity: Not classified as hazardous.

Carcinogenicity: Not classified as hazardous.

Reproductive toxicity: Not classified as hazardous.

STOT-single exposure: Not classified as hazardous.

STOT-repeated exposure: Not classified as hazardous.

Aspiration hazard: Not classified as hazardous.

11.2 Information on other hazards

Information on other hazards See in section 2.3

Other hazards No information.

SECTION 12: Ecological information

12.1. Toxicity

Not classified as hazardous.

General information: No information.

12.2. Persistence and degradability

General information: No data.

12.3. Bioaccumulative potential

General informations: No information.

12.4. Mobility in soil

- Air: According to its physical properties, the substance evaporates

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



quickly from an aqueous environment, thus neither acute nor chronic effects practically could not be observed.

- Water: Evaporates quickly from water and soil.
- Soil: Evaporates quickly from water and soil.

12.5. Results of PBT and vPvB assessment

PBT- and vPvB-assessment: No information.

12.6. Endocrine disrupting properties

See in section 2.3

12.7. Other adverse effects

None.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Should not be released into the environment. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Material:

Avoid discharge to atmosphere.

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. Render harmless by incineration.

Contaminated packaging:

Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14: Transport information

14.1. UN-number

UN-number: UN2037

14.2. UN proper shipping name

International transport: RECEPTACLES, SMALL, CONTAINING GAS (GAS CARTRIDGES)

14.3. Transport hazard class(es)

Classification code: 5F

Labels: 2.1

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



14.4. Packing group

None.

14.5. Environmental hazards

ADR/RID None.

IMDG None.

ADN None.

14.6. Special precautions for user

ADR/RID Transport category: 2
Tunnel restriction code: (D)
Hazard identification No.: –
Limited quantities: 1 L
Excepted quantities: E0
Special provision(s): CV9 CV12 S2

IMDG EMS Code: F-D, S-U
Stowage category: Category B SW2
Properties and notices: Normally contain mixtures of liquefied butane and propane in various proportions for use in camping stoves, etc.

ICAO Limited quantity: 1 KG (Y203)
Passanger and Cargo Aircraft: 1 KG (203)
Cargo Aircraft only: 15 kg (203)

14.7. Transport in bulk according to IMO regulations

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC
- COMMISSION REGULATION (EU) 2020/878 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

SAFETY DATA SHEET


according to Regulation (EC) 1907/2006 and Regulation (EC) 2015/830

R134a, R1234yf, R406, R409, R413 Drop-In replacement refrigerant mixture

Issue date: 09. 08. 2019

Revision: 29.03.2022

Version: 2.00



- REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006
- Regulation (EC) No 2037/2000 of the European Parliament and of the Council of 29 June 2000 on substances that deplete the ozone layer

15.2. Chemical safety assessment

No information.

SECTION 16: Other information

The full H-statements from the Section 2. and 3:

- | | |
|------|---|
| H220 | Extremely flammable gas. |
| H280 | Contains gas under pressure; may explode if heated. |

The full abbreviation from the Section 2. and 3:

- | | |
|------------|--------------------|
| Flam. Gas | Flammable gas |
| Press. Gas | Gas under pressure |

Used evaluation of hazard information:

According to Regulation (EC) 1272/2008 Article 9 for the classification used paragraph 1. and 5.

Modified sections:

Section 2: changed P-phrase P211 → P403

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfill his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of safety data sheet.